




BEC 4000 is a high-performance Wi-Fi6 mesh router, supports MU-MIMO allowing multiple devices to access the network at the same time with equal and full speed, ensure the simultaneous and stable connection of multiple devices.

BEC 4000 provides gigabit network interface, supports 2.4G and 5G wireless network, wireless transmission rate can reach up to 3000Mbps, and supports rich software features, as a new generation of Wi-Fi6 products, for enterprises and families better online experience.

Mesh Router .....

Move freely from room to room on a single network with WiFi Mesh Routers uninterrupted

- Avoid Downtime
- Easy Installation
- Increase Efficiency
- Expand Reception



## **Key Features**

- Full compliant with IEEE802.11a/b/g/n/ac/ax
- Smart Mesh networking
- Complies with IEEE802.11k/v/r
- EasyMesh is a scalable system, whole-home coverage and a consistently strong signal, without limited coverage or disconnection
- Dual-band OFDMA allowing for a higher density of simultaneous users
- Support MU-MIMO, simultaneous connection of multiple devices
- Support WPA3, and the latest and most advanced Wi-Fi security protocol
- Support WPS allow access to your home network more safely and easily
- 2400Mbps on 5GHz and 600Mbps on 2.4GHz band for total 3000Mbps simultaneously
- Using a centralized management backstage, you can easily manage all mesh grid nodes and set different network rules for devices accessing the network, such as guest network, parental controls, Qos
- Intelligent beamforming delivers highly targeted and efficient Wi-Fi connection
- Wireless roaming helps users auto switch to stronger signal source

## **AX3000 Dual Band Wi-Fi6 Mesh Router**



## **Specifications**

Basic Parameters	i
Chipset	BCM6756+BCM53134
CPU	Quad Core A7 1.7GHz, DMIPS 12600
DRAM	DDR3 256MB
Flash	128MB
Standards	IEEE802.11a/n/ac/ax @5GHz, IEEE802.11b/g/n/ax @2.4GHz
Signal Rate	5GHz (2x2): Up to 2400Mbps, 2.4GHz (2x2): Up to 600Mbps
Wireless Security	WPA2-PSK, WPA3-SAE, WPA2- PSK/WPA3-SAEencryption

Hardware	
Interface	1 x 10/100/1000 Mbps WAN Port 3 x 10/100/1000 Mbps LAN Port 1 x DC Port
Button	WPS/Mesh Button, RESET Button
Power Supply	DC 12V1A
Antenna	4 x 3 dBi Internal antennas
LED	PWR, Wi-Fi, WPS/Mesh
Dimensions	140mm*53mm*180mm(L*D*H)

Environment	
Operating Temperature	0°C~40 °C
Storage Temperature	-40°C~70°C
Relative Humidity	10%~90%, non-condensing
Storage Humidity	5%~95%, non-condensing

Software Features		
WAN Type	Dynamic IP/ Static IP/ PPPoE	
DHCP	Server, Client, DHCP Client List, Address Reservation	
Quality of Service	WMM, Bandwidth Control	
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ, DDNS	
Access Control	Parental Control, Local Management Control, Access Schedule, Black List	
Firewall Security	DoS, IP Address Filter/MAC Address Filter/Website Filter, AP Isolation	
Internet Protocol	IPv4, IPv6	
Management	Access Control, Local Management, Remote Management, TR-069,	
Mesh	IEEE802.11k/v/r, Network Topology, EasyMesh, Seamless Roaming	
Wireless	Guest Network, Timing Off, Multi - frequency integration, MU-MIMO, Hidden SSID, WPS	
Device Management	Reboot, Restore Factory, Beckup/Restore, Timing Reboot, Firmware Upgrade	
Monitoring	CPU Utilization, CPU Temperature, Memory Utilization, Flow, Upload/Download Rate	
Other	NAT, Indicator switch, System Log, Speed Test, Channel analysis, Signal Power Regulation	

Package Contents		
Power Adapter	1 x Power Adaptor	
Router	1 x Wi-Fi Router	
User Manual	1 x Quick Installation Guide	
Accessories	1 x Ethernet Cable	

## Connection

